



Grey 8

Overview

Grey 8 is a professional 8 Mic/line input mixer with balanced XLR/TRS jacks & insert points and 4 stereo inputs that features a 3 band semi-parametric intermediate frequency scan EQ, that is adjustable from 140 Hz to 3 kHz. The desk provides 4 sets of AUX assistant outputs, which can be chosen as PRE-F(return) or PST-F(connect outside processor). **Grey 8** has a built-in professional digital effects unit. Thanks to its low-noise preamplifiers the desk provides exceptional sound clarity with strong anti-interference ability and 48V phantom power on every microphone input. Every channel is equipped with an output connector that can be sent to n-Track Studio(PRE-F) or effect equipment(PST-F).

Specifications

General

Mono Channels: 8
Stereo Channels: 4
Input sensitivity: Mic: +17dB / Line:+30dB / Stereo:+30dB
THD: <0.008%, +4 dBu @ 1KHz, unity gain
Gain Control:
- Mono: -51dB~0dB
- Line: -26dB~0dB
Input impedance:
- Mic: ~2 KOhm
- Mono: >40 KOhm
- Stereo: >30 KOhm
- Stereo returns: >10 KOhm
Residual output noise: <-83dBu

Crosstalk: <-79dBu
Earphone output power: 260mW
Impedance output: < 75-Ohm
Signal-to-Noise ratio: <0.01% @-30dB input to MIX,
MIC gain at 30 dB
Frequency Response: 20-20KHz
Max output level: +20dB
+48V phantom power
1 Monitor output

Per channel

Mic Input: Electronically balanced XLR
Line Input: TRS 1/4" Plug
Insert input: TRS 1/4" Plug
Stereo inputs: 2 RCA/2 TRS 1/4" Plug

Equalization:
- HF: 12KHz ± 15dB
- MF: 240Hz-6KHz ± 15dB
- LF: 60Hz ± 15dB
Low-noise preamplifier with strong anti-jamming power
4 groups of AUX output - Pre & Post fader
Mute selector
Signal & Peak indicator

Electrical

Input voltage range: AC100~240V, 50-60Hz
Power consumption: 35W