



FlatparTEC

Overview

FlatparTEC is an ultra-slim Led Par powered by 150 RGB (48R, 51G, 51B) 10 mm. LEDs with smooth RGB color mixing in a slim & light design. With its completely silent operation and a 30 degrees beam angle it's ideal for architectural applications. **FlatparTEC** is designed to give you great flexibility with its 6 operational modes (Built-in programs, DMX mode, M/S, auto run, sound active, static colors), making it the ideal solution for any given application.

Specifications

Source & Optics

Light Source: 150 x RGB (48R, 51G, 51B) 10 mm. LEDs

LEDs life: 50,000 hours

Beam angle: 30° (20° & 40° optional)

Photometric data

Luminous Flux: 138 lux @ 5m (16 ft.)

Effects & Functions

Smooth RGB mix

Dimmer: Full range 0-100% general & for all three colors

Strobe effect

Flicker free

Control

DMX channels: 3/4/8

Operational modes: DMX, Master/Slave, Auto-run, Static colors, Sound-active & Built-in programs

Electrical

Input voltage range: AC100-240V, 50-60Hz

Power consumption: 20W

Physical

4-digit LED display

DMX connectors: 2 XLR connectors (XLR-3 In and Out)

Power supply connectors (In/Out)

Dimensions: 260x68x210 mm. / 10.2x2.6x8.2 in.

Weight: 1.8 Kg. / 4 Lbs.