



FlattriTEC

Overview

FlattriTEC is an ultra-slim Tri-Led Par powered by 7 x tri-3W LEDs, sporting tri-color LED technology, that enables a smooth RGB mix with no multicolor shadows. Packed in a slim & light design with completely silent operation and a 40 degrees beam angle it's ideal for architectural applications. **FlattriTEC** is designed to give you great flexibility with its 6 operational modes (Built-in programs, DMX mode, M/S, auto run, sound active, static colors), making it the ideal solution for any given application.

Specifications

Source & Optics

Light Source: 7 x 3W 3-in-1 LEDs
LEDs life: 50,000 hours
Beam angle: 40° (25° optional)

Photometric data

Luminous Flux: 217 lux @ 5m (16 ft.)

Effects & Functions

Tri-color LED technology: Smooth RGB mix with no multi colored shadows
Dimmer: Full range 0-100% general & for all three colors

Strobe effect
10 built-in programs
Flicker free

Control

DMX channels: 3/4/8
Operational modes: DMX, Master/Slave, Auto-run, Static colors, Sound-active & Built-in programs

Electrical

Input voltage range: AC100-240V, 50-60Hz

Power consumption: 30W

Physical

4-digit LED display
DMX connectors: 2 XLR connectors (XLR-3 In and Out)
Power supply connector
Dimensions: 267.5x255x97 mm. / 10.5x10x3.8 in.
Weight: 2.2 Kg. / 4.8 Lbs.