



Fenix 108 System

Overview

Fenix 108 System is an ultra-compact full range system that comprises a 1 x 8" subwoofer unit with integrated amplifier and 2 x 4" full-range satellite speakers, sporting a total system output power of 260W (RMS) at a frequency response of 40Hz-20kHz. The unit has a durable plywood housing and the included carrying bag make the **Fenix 108 System** an ideal system for mobile use.

Specifications

Fenix 108A – Subwoofer unit

Component: 8" Woofer
Power output: 100W (RMS)
Maximum SPL: 116 dB (1W/1m)
Frequency response: 40Hz-125Hz (-3dB)

Fenix 204 – Full range speakers

Components:

- LF: 2 x 4" woofers
- HF: 1" dome tweeter
Power output: 80W (RMS)
Impedance: 4-Ohm
Maximum SPL: 112 dB (1W/1m)
Frequency response: 80Hz-20kHz (-3dB)

Input connectors: 1 x NL4

Amplifier & Control

Passive speaker output: 2 x 60W (RMS) @ 4 ohms
Input connectors: XLR/TRS 1/4" Combo (balanced) & dual-RCA (unbalanced)
Output connectors: 2 x NL4
Crossover frequency: 120Hz
Control: Master Volume & Bass Volume
Phase inverter
Power, Signal & Clip indicators
Power consumption: 275W

Input voltage range: AC100–240V, 50-60Hz

Physical

- Fenix 204
Dimensions: 144x172x360 mm. / 5.65x6.75x14 in.
Weight: 3 Kg. / 6.6 Lbs.
- Fenix 108A
Dimensions: 360x300x435 mm. / 14x12x17 in.
Weight: 11.5 Kg. / 25.3 Lbs.