



# Neo 600 Led

### **Overview**

**Neo 600 Led** is a wash moving head powered by 12 x 15W RGBW 4-in-1 LEDs with an 8° beam angle or 15° field angle that features quad-color LED technology, enabling a smooth RGBW mix with no multicolor shadows. The unit has an adjustable color temperature from 2500K to 8000K and provides general dimming and blackout for all four colors plus strobe effect. Additionally, **Neo 600 Led** gives you pixel ring control.

## **Specifications**

#### **Source & Optics**

Light Source: 12 x 15W 4-in-1 LEDs LEDs life: 50.000 hours Beam angle: 8° Field angle: 15°

Photometric Data Luminous Flux: 15700 lux @ 3m (10 ft.)

#### **Effects & Functions**

Quad-color LED technology: Smooth RGBW mix with no multi colored shadows Color temperature linear adjust from 2500K to 8000K Color macros Dimmer: Full range 0-100% general & for all four colors



Strobe effect: 1-25 flashes per second LED Ring control Flicker free 7 pre-built programs

#### Control

DMX channels: 15/17/21 Wireless DMX (Optional) Remote DMX addressing, lamp on/off, reset, sound control switch by DMX controller Advanced RDM function Software upgrade via DMX (with optional accessory)

#### Movement

Pan: 540° / 630° Tilt: 265°

WWW.AMPROWEB.COM

8 & 16-bit resolution Auto repositioning

#### Electrical

Input voltage range: AC100–240V, 50-60Hz Power consumption: 285W

#### Physical

LCD graphic display DMX connectors: 4 XLR connectors (XLR-3 In and Out; XLR-5 In and Out) Power supply connectors: POWERCON® In/Out Dimensions: 400x267x230 mm. / 15.7x10.5x9 in. Weight: 10 Kg. / 22 Lbs.

Ū

/amprogroup