



MoonTEC IV

Overview

MoonTEC IV is a LED effect powered by 256 RGBWY (64R, 64G, 64B, 32W, 32Y) 5 mm. LEDs, sporting built-in dynamic & static effects, that really make the unit stand out. The unit has a 37° beam angle and provides an amazing strobe function. **MoonTEC IV** is designed to give you great flexibility with its 6 operational modes (built-in programs, auto running, DMX mode, M/S, sound-active, static color) and all-night operation, making it the ideal solution for any given application.

Specifications

Source & Optics

Light source: 256 x RGBW (64R, 64G, 64B, 64W) 5 mm. LEDs
LEDs life: 100,000 hours
Beam angle: 37°

Photometric data

Luminous Flux:
- Red - 913 lux @ 2m (6 ft.)
- Green - 1091 lux @ 2m (6 ft.)
- Blue - 1354 lux @ 2m (6 ft.)
- White - 914 lux @ 2m (6 ft.)

Effects & Functions

Moonflower effect
Strobe effect
Built-in programs and effects called up via DMX

Control

Operational modes: DMX, Master/Slave, Auto-run, Static colors, Sound-active & Built-in programs
DMX channels: 3/4

Electrical

Input voltage range: AC 100–240V, 50-60Hz
Power consumption: 52W

Physical

4-digit LED display
DMX connectors: 2 XLR connectors (XLR-3 In and Out)
Dimensions: 302x302x241 mm. / 11.8x11.8x9.48 in.
Weight: 3.2 Kg. / 7 Lbs.