



EDGE 12 SUB

Overview

EDGE 12 SUB is a self-powered 12" subwoofer with a 3.5" voice coil that delivers 350W continuous @ 4-ohm. As a fundamental part of the EDGE system, this subwoofer is compatible both with the **EDGE 25** and **EDGE 84**, with the capacity to send a cutted & amplified signal only selecting the model on its rear panel. Thanks to its D-type amplification, **EDGE 12 SUB** achieves great power with very good sound quality. A frequency response ranging from 40Hz to 500Hz coupled with a very complete control panel and a high efficiency protection circuit completes the most remarkable features of an equipment ideal for small and medium scale applications.

Specifications

Components

LF: 1 x 12" Woofer with 3.5" voice coil

Features

Self-powered 12" Subwoofer
3 selectable modes: Edge 25, Edge 84 & user
Frequency response (-6dB): 40Hz-500Hz
Sensitivity (1W/1m): 96 dB
Cooling: Temperature-controlled fan
Enclosure design: Plywood cabinet, resistant black paint, metal grille with foam & rubber feet

Mounting: One metal standard pole-mount

Amplifier & Control

Power output: 350W (continuous) @ 4-ohm
Amplifier type: Class D
Protections: Thermal DC / Overload / Digital Compressor / Limit
Controls: Volume Control / Switch for Input sens / Switch for mode selector / Ground Lift / IP Control
Input voltage range: AC100-240V, 50-60Hz

Connectors

Inputs:
2 XLR-3/Plug combo
1 L/R RCA
Output: 1 NL4 Speakon
Link: 1 XLR-3
IP Control: RJ-45

Physical

Dimensions: 430x450x480 mm. / 17x17.7x19 in.
Weight 20.5 Kg. / 45.22 Lbs.